

Water touches so much of your life.

The MBA Series® **Residential Water Softeners**

**BUILT TO GIVE YOU THE BEST QUALITY
WATER FOR YOUR FAMILY.**

- **MONEY SAVING**
- **SALT SAVING**
- **WATER SAVING**
- **EFFICIENT**
- **RELIABLE**
- **EASY TO USE**
- **SMART TECHNOLOGY**
- **12 YEAR WARRANTY**
- **TURBULATOR TO EXTEND
MINERAL LIFE**
- **FACTORY SUPPORT FOR
THE LIFE OF THE UNIT**

Quality That Lasts!



MA **MASTER**
Water Conditioning Corp.



ECONOMIC ELECTRONIC TIME CLOCK

Fully programmable cycle times,
regeneration by frequency or day of week.
High efficiency regeneration sequence.

HISTORY

Easily program unit to tell you when
service is required. Readily accessible
historical performance and diagnostic data
available at your fingertips.

TOUCH OF CONVENIENCE

The control valve is factory-programmed
with complete salt tables and operational
parameters. Simply set the timing
schedule and hardness data...

IT'S THAT EASY

FEATURES



**WARRANTY


One of the best in the business!
12 year warranty on mineral and
brine tanks. 5 year warranty
on valves.

MEMORY RETENTION

Battery-free time & date retention
during loss of power failure.
Up To 8 Hours!

FACTORY SUPPORT

Factory technical service is
available to your dealer or
distributor for the life of the unit.



MBA® Control Valve Bypass Valve

Series MBA Automatic, 5-cycle Softener Control constructed
of non-corrosive Noryl®. The control valve automatically starts a
regeneration cycle whenever you choose. The MBA control
valve is designed with a unique cam assembly that makes
servicing the unit a snap! The MBA control valve is
guaranteed for 5 years. **


SOFTENER RESIN

The cation softening resin used in our
softeners is designed to perform efficiently
for years. It's one of the most efficient and
rugged water softening resins available.

OPTIONAL:

The 434 safety shutoff provides a positive
air check and brine water level control.

The 464 safety shutoff is standard
on all 1" control valves or with
a 400 lb. salt tank.



TURBULATOR

A plastic distributor system that uses a unique
Water-Stream Compression device to shoot the
softening resin granules to the top of the softener bed.
This agitation extends the life, hardness,
and iron removal capacities of the softening resin.

**Detailed warranty information accompanies each water conditioner.

SPECIFICATIONS

Model No.	Grains Capacity Per Regeneration	Service Flow GPM	Salt Storage LBS.	Salt Usage Per Regeneration LBS.	Backwash Flow GPM	Service Pipe Size	Drain Pipe Size	Floor Space		Height	Shipping Weight LBS.
								Width	Depth		
MBA-30T	30,000	8.5	300	15.0	2.5	3/4"	3/8"-1/2"	31"	19"	48"	95
MBA-45T-1	45,000	8.5	400	22.0	2.5	1"	3/4"	31"	19"	62"	130
MBA-60T-1	60,000	12.0	400	30.0	4.0	1"	3/4"	33"	19"	54"	180