

# MUN SERIES

## Automatic Upflow Neutralizers



***Caution: The Upflow Series Acid Neutralizers are designed to be used on clear water applications only (less than 5 NTU Turbidity and .5 ppm Iron). Failure to do so could result in a pressure loss, cloudy water and possibly void the warranty.***

### FEATURES:

These units allow the low pH water to travel upflow through a neutralizing mineral without the need for backwashing.

Uses a state of the art Inlet/top Outlet valve made of durable Noryl. The valve is engineered and designed to handle high flow rates, which means less water pressure and flow loss at your plumbing fixtures. The valve also incorporates a bypass valve that provides you with a quick way to divert water from passing through the system. All components are constructed of high quality non corrosive materials.

Each unit is equipped with a special upper distributor system to prevent the loss of neutralizing mineral during service.

1" distribution tube.

### BENEFITS:

Dome plug to allow adding mineral to the system without dismantling any parts or piping.

Great for situations where small amounts of water prevents the use of a backwashable neutralizer.

## SPECIFICATIONS

MODEL	MINERAL	Capacity Cu. Ft.	Service Flow Rate	Pipe Size In/Out	Tank Size Inches
MUN-10 BY	1 CF Calcite .5 CF NS Mix	1.5 CF	5.0	3/4" -1"	10 X 54
MUN-1040 BY	.5 CF Calcite .5 CF NS Mix	1.0 CF	5.0	3/4" -1"	10 X 40
MUN-13 BY	2 CF Calcite	2.0 CF	7.0	3/4" -1"	13 X 54
MUN-16 BY	.5 CF Calcite .5 CF NS Mix	1.0 CF	10.0	3/4" -1"	16 X 23
MUN-1665 BY	4 CF Calcite	4.0 CF	10.0	3/4" -1"	16 X 65



[www.masterwater.com](http://www.masterwater.com)