The IC2.0 System by Hellenbrand

A Simple Solution for Sulfur Odor and Iron Removal

BUILT TO GIVE YOU THE BEST QUALITY WATER FOR YOUR FAMILY.

- MONEY SAVING
- EFFICIENT
- RELIABLE
- EASY TO USE
- SMART TECHNOLOGY
- 12 YEAR WARRANTY
- FACTORY SUPPORT FOR THE LIFE OF THE UNIT
- Removes sulfur odor with no chemicals, no air Injectors, venturis or micronizers.
- * Removes concentrations of dissolved and precipitated

iron.

Quality That Lasts!







FACTORY SUPPORT

Factory technical service is available to your Dealer or Distributor for the life of the unit.

HISTORY

Easily program unit to tell you when servicing is required. Readily accessible historical performance and diagnostic data available at your fingertips.

FEATURES



ECONOMIC ELECTRONIC TIME CLOCK

Fully programmable cycle times, regeneration by frequency or day of week. High efficiency regeneration sequence.

**WARRANTY

One of the best in the business! 12 Year warranty on Mineral and Brine tanks. 5 year warranty on

MEMORY RETENTION

Battery-free time & date Retention during loss of Power failure.... Up To 8 Hours!



263 Control Valve **Bypass Valve**

Series 263 Automatic, 3-Cycle Filter Control constructed of Non-corrosive Noryl®. The control valve automatically starts a regeneration cycle whenever you choose. The 263 control

valve is designed with a unique cam assembly that makes servicing the unit a snap! The 263 control valve is guaranteed for 5 years.*



Mineral-rich water is forced through an aeration tank which converts dissolved minerals such as iron, manganese and sulfur into physical particles.

These tiny mineral particles are then circulated in the system for enough time to grow to a size where they are then trapped in the filter tank.

Then the Iron Curtain system then removes these minerals, leaving clean, odor free, good tasting water.



A detailed water analysis must be performed to assure proper system performance

Specification Reference Table

Model #	Conditioned Water Flow Rate	Backwash Flow Rate	Backwash Timing	Slow Rinse Timing	Fast Rinse Timing
IC-2.0-1054	5.0 gpm	5.0 gpm	20 Minutes	0 Minutes	12 Minutes
IC-2.0-1248	8.0 gpm	8.0 gpm	20 Minutes	0 Minutes	12 Minutes
IC-2.0-1354	10.0 gpm	10.0 gpm	20 Minutes	0 Minutes	12 Minutes